



WEPAK
CORPORATION[®]

ACRYLIC FLOOR FINISH

GENERAL INFORMATION

A premium floor finish that is ultra-durable. Give Brilliant initial gloss, and can be buffed or burnished. Our proprietary formulation balances brilliant clear gloss with super tough polymer protection.

DIRECTIONS

Preparations fo Floor: Follow recommended dilution of stripper. Strip floor thoroughly of old was of floor finish. For heavy buildup areas, such as baseboards, under desks, etc., you may have to apply more stripper to the floor as the stripper solution becomes diluted with old loosened finish. Rinse the floor as thoroughly as possible with clear water and allow to dry.

Application of Finish: Work with clean equipment. Before use, soak mops in water and wring out tightly, so they absorb less finish and are easier to clean. Apply finish in uniform light to medium coats. Coat traffic lanes more than other areas and work additional coats toward the edges. Recommended application for every three coats in traffic areas apply oe coat to non-traffic areas.

Cleaning/Maintenance: Daily sweeping and dust mopping is critical for any floor care program. Damp mopping with a neutral cleaner and following the recommended dilutions of the product as required are also needed. Before spray buffing or high burnishing the floor need to be cleaned with either of the previous directions. This product may also be used to extend the life of the finish by recoating periodically.

SPECIFICATIONS

Type.	Finish
Color.	Milky White
Physical State.	Liquid
Odor.	Light Ammoniacal
Specific Gravity.	1.03
Solubility (in water).	Infinite
Flammability (Flash Point).	Non-Combustible
pH.	8.0-8.5

MANUFACTURED BY

WEPAK
CORPORATION[®]

P.O. BOX 36803
CHARLOTTE, NC 28236
(704) 334-5781

CALL TOLL FREE
1(800)438-4270
FAX NUMBER
1(704)343-9757