Fire Hazard **National Fire Protection** Health Reactivity **Association (NFPA)**

7732-18-5

60-100

Hazardous Material Information System (HMIS)

Health 3 Fire Hazard 4 Reactivity 0

851-7145

Specific Hazard

Protective Clothing

Phone: (888) 352-2249



Emergency Overview

Tan. Aerosol. See Section 9. DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.

Section 1. Chemical Product and Company Identification				
Product Name	MR. MUSCLE O	VEN AND GRILL CLEANER	_ Code	91206
	AEROSOL			
Product Use	Industrial/Institutional: C	leaning product.	PMS#	433200
SDS#	126040003		Validation Date	3/7/2002
U.S. Headquarter	°S	Product Distributed by:	Print Date	3/7/2002
Drackett Profess	ional			
A Division of S.C. Johnson Commercial Markets, Inc.		Commercial & Industrial Suppli		3/7/2002.
8310 16th Street		Dodge Packaging Specialties, Inc	In Case of	(800) 851
Sturtevant, Wisconsin 53177-0902		Specialties, Inc	Emergency	` '

Section 2. Composition and Information on Ingredients Ingredients CAS# % by Weight **Exposure Limits** LC50/LD50 Monoethanolamine 141-43-5 1-5 **OSHA (United States).** ORAL (LD50): Acute: 1720 TWA: 8 mg/m³ mg/kg [Rat]. DERMAL (LD50): STEL: 15 mg/m³ Acute: 1018 mg/kg [Rabbit]. ACGIH (United States). TWA: 7.5 mg/m³ STEL: 15 mg/m³ OSHA (United States). Butane 106-97-8 1-5 Not available. TWA: 1900 mg/m³ ACGIH (United States). TWA: 1900 mg/m³ Isobutane 75-28-5 Not available. VAPOR (LC50): Acute: 0.0057 1-5 ppm 0.25 hour(s) [Rat]. Sodium Hydroxide 1310-73-2 1-5 **OSHA (United States).** Not available. CEIL: 2 mg/m³ ACGIH (United States). STEL: 2 mg/m³ Diethylene Glycol Butyl Ether Not available. 112-34-5 10-30 ORAL (LD50): Acute: 5660 mg/kg [Rat]. DERMAL (LD50): Acute: 2700 mg/kg [Rabbit]. Water Not available

1-800-882-1003 • 828-369-7584 Franklin, NC Visit us online www.dodgepackaging.net

on. Skin contact. Eye contact.	
Potential Acute Health Effects	
ve. May cause permanent damage including blindness.	
ve. May cause permanent damage.	
use irritation and corrosive effects to nose, throat and respiratory tract.	
ve. May cause burns to mouth, throat, and stomach.	
ι	

Not available.

Medical Conditions Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may Aggravated by Overexposure: be more susceptible to irritating effects.

See Toxicological Information (section 11)

Section 4. First Aid Measures	
Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures		
Flammability of the Product Flash Points	NFPA 30B Level 1 Aerosol. CLOSED CUP: <-7°C (19.4°F).	
Products of Combustion	None known.	
Fire Fighting Media and Instructions	Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. Fight fire from protected location or maximum possible distance. In case of fire and/or explosion do not breathe fumes.	
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).	
Special Remarks on Fire and Explosion Hazards	Aerosol product - Containers may rocket or explode in heat of fire. Corrosive material (See sections 8 and 10).	

Section 6. Accidental Release Measures	
Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.

Section 7. Handling and Storage		
Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Use only in well-ventilated areas. Do not puncture or incinerate. FOR INDUSTRIAL USE ONLY.	
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. Keep away from heat, sparks and flame. Pressurized container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN.	

Section 8. Exposure Controls/Personal Protection		
Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.	
Personal Protection		
Eyes	Chemical splash goggles.	
Hands	Chemical resistant gloves. Includes: Neoprene gloves. Rubber gloves.	
Respiratory	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.	
Feet Protective footwear.		
Body	If major exposure is possible, wear suitable protective clothing and footwear.	

Section 9. Physical and Chemical Properties

Physical State and

Appearance

Liquid. (Aerosol.)

Odor Citrus.

Color Tan.
pH 13 [Basic.]

Specific Gravity 1

Boiling/Condensation Point100°C (212°F)Melting/Freezing Point0°C (32°F)Viscosity300 cP (Dynamic).

Solubility in water Complete.

Section 10. Stability and Reactivity

Stability and Reactivity
Conditions of Instability
The product is stable.
Excessive heat.

Incompatibility with Various Substances

Reactive with acids.

Hazardous Decomposition

Products

When exposed to fire: Produces normal products of combustion. Toxic decomposition products include:

Oxides of sodium.

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

Acute toxicity Corrosive.

Effects of Chronic Exposure None known.

Other Toxic Effects

Contains approximately 0.1% Cristobalite (CAS# 14464-46-1), NJ, PA, MA, NTP. This formulation is a heavy, viscous liquid. Therefore, respirable-size particles of dry Cristobalite are not expected to become

airborne and will not be inhaled.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. If

possible, recycle empty aerosol cans to the nearest steel recycling center. Use up package or give to

someone who can. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Please refer to the Bill of Lading/receiving documents for up to date shipping information. **Shipping Name**

TDG Classification

TDG Proper Shipping Name TDG Class Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal Clean Water Act (CWA) 311: Sodium hydroxide

Clean air act (CAA) 112 accidental release prevention: Butane

Clean air act (CAA) 112 regulated flammable substances: Butane, Isobutane

CERCLA: Hazardous substances.: Diethylene Glycol Butyl Ether, Isobutane, Sodium hydroxide

State New Jersey spill list: Diethylene Glycol Butyl Ether, Sodium hydroxide

New Jersey: Monoethanolamine, Diethylene Glycol Butyl Ether, Butane, Isobutane, Sodium hydroxide

Massachusetts spill list: Monoethanolamine, Butane, Isobutane, Sodium hydroxide Massachusetts RTK: Monoethanolamine, Butane, Isobutane, Sodium hydroxide

Pennsylvania RTK: Monoethanolamine, Diethylene Glycol Butyl Ether, Butane, Isobutane, Sodium

hydroxide

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Not applicable.

Information

Canadian Regulations

WHMIS Classification CLASS A: Compressed gas. CLASS E: Corrosive liquid.

WHMIS Icon

Information

Registered Product Not applicable.

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information

Other Special

SDS Serial Range: 001-003

Considerations

Version 1.01

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.